



# SolarEdge Three Phase Inverters (South Korea)



## The best choice for SolarEdge enabled systems

- Superior efficiency (98%)
- Small, lightest in its class, and easy to install
- Built-in module-level monitoring
- Communication to internet via Ethernet or Wireless
- IP65 – Outdoor and indoor installation



*architects of energy™*



# Three Phase Inverters

SE10.5k-KOR/SE12.5k-KOR/SE15k-KOR/SE16k-KOR/ SE17k-KOR

All our solar inverters are part of SolarEdge's innovative system designed to provide superior performance at a competitive price. The SolarEdge PV inverter combines a sophisticated, cutting-edge digital control technology and a one stage, ultra-efficient power

conversion architecture to achieve superior performance – over 97% efficiency and best-in-class reliability. Our fixed-voltage technology ensures the inverter is always working at its optimal input voltage, regardless of the number of modules or environmental conditions.

## TECHNICAL DATA

	SE10.5k-KOR	SE12.5k-KOR	SE15k-KOR	SE16k-KOR*	SE17k-KOR*	
<b>OUTPUT</b>						
Rated AC Power Output	10500	12500	15000	16000	17000	VA
Maximum AC Power Output	10500	12500	15000	16000	17000	VA
AC Output Voltage - Line to Line / Line to Neutral (Nominal)	380 / 220					Vac
AC Output Voltage - Line to Neutral Range	193 - 264.5					Vac
AC Frequency	60 ± 5					Hz
Maximum Continuous Output Current (per Phase)	17	20	23	25.5	26	A
Residual Current Detector / Residual Current Step Detector	300 / 30					mA
Grids Supported - Three Phase	3 / N / PE ; 230 / 400					V
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes					
<b>INPUT</b>						
Recommended Maximum DC Power ** (Module STC)	11500	13700	16500	17600	18700	W
Transformer-less, Ungrounded	Yes					
Maximum Input Voltage	950					Vdc
Nominal DC Input Voltage	750					Vdc
Maximum Input Current	17.5	21	22	23	23	Adc
Reverse-Polarity Protection	Yes					
Ground-Fault Isolation Detection	1MΩ Sensitivity					
Maximum Inverter Efficiency	98					%
European Weighted Efficiency	97.5	97.4	97.4	97.4	97.4	%
Nighttime Power Consumption	< 2.5					W
<b>ADDITIONAL FEATURES</b>						
Supported Communication Interfaces	RS485, RS232, Ethernet, Zigbee (optional)					
<b>STANDARD COMPLIANCE</b>						
Safety	IEC-62103 (EN50178), IEC-62109					
Grid Connection Standards	VDE 0126-1-1, VDE-AR-N-4105, AS-4777, RD-1663, DK 5940					
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B					
RoHS	Yes					
<b>INSTALLATION SPECIFICATIONS</b>						
AC Output	Cable Gland - diameter 11-17					mm
DC Input	MC4					
Dimensions (HxWxD)	540 x 315 x 260					mm
Weight	32					kg
Operating Temperature Range	-20 - +60					°C
Cooling	Fan (user replaceable)					
Protection Rating	IP65 - Outdoor and Indoor					
Bracket Mounted (Bracket Provided)						

\* Certification pending.

\*\* Higher input DC power may be installed; analyze yearly AC performance.

■ USA ■ Germany ■ Italy ■ France ■ Japan ■ China ■ Israel

[www.solaredge.com](http://www.solaredge.com)



**solaredge**  
architects of energy™