



SolarEdge Power Optimizer Module Embedded Solution




A superior approach to maximizing the throughput of photovoltaic systems using module embedded electronics

- Up to 25% increase in power output
 - Superior efficiency (99.5%) - peak performance in both mismatched and unshaded conditions
 - Flexible system design for maximum space utilization
 - Next generation maintenance with module-level monitoring and smart alerts
 - Unprecedented installer and firefighter safety
-
- **Embedded into any module as a certified junction box**
 - **Faster installation, less wiring and better roof utilization**
 - **Electric arc detection and termination**



architects of energy™



SolarEdge Power Optimizer

Module Embedded Solution

PB250-CSI
PB350-CSI

HIGHLIGHTS

- Module level MPPT - optimizes each module independently
- Dynamically tracks the global maximum operating point for both modules and inverter
- Module-level monitoring for automatic module and string level fault detection allowing easy maintenance
- Electric arc detection and termination - reduces fire hazards
- Unprecedented installer and firefighter safety mode - safe module voltage when inverter is disconnected or off
- Up to 4 sub-string inputs with bypass diodes
- Removes manufacturer limitations - no more temperature variance, cell mismatch and manufacturing variations
- Lower installation costs with faster design, less wiring, DC disconnects and fuses
- Easy and flexible installation – use the same installation methods as exist today
- Allows parallel uneven length strings and multi-faceted installations
- Allows connection of different module types simplifying inventory considerations
- Immediate installation feedback for quick commissioning

TECHNICAL DATA

INPUT		
Rated Input DC Power	250/350	W
Absolute Maximum Input Voltage (Voc)	60	Vdc
MPPT Operating Range	5 - 60	Vdc
Maximum Input Current	10	Adc
Reverse-Polarity Protection	Yes	
Maximum Efficiency	99.5	%
European Weighted Efficiency	98.8	%
CEC Weighted Efficiency	98.7	%
Nighttime Power Consumption	0	W
Overvoltage Category	II	
OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING INVERTER)		
Maximum Output Current	15	Adc
Operating Output Voltage	5 - 60	Vdc
Total Maximum String Voltage (Controlled by Inverter) - US and EU 1-ph	550	Vdc
Total Maximum String Voltage (Controlled by Inverter) - EU 3-ph	950	Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM INVERTER OR INVERTER OFF)		
Safety Output Voltage per Power Optimizer	1	Vdc
PV SYSTEM DESIGN		
Minimum String Length	8 (1ph system) / 15 (3ph system)	modules
Maximum String Length	module power dependant; typically 20 - 25 (1ph system) / 45 - 50 (3ph system)	modules
Parallel Strings of Different Lengths or Orientations	Yes	
STANDARD COMPLIANCE		
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3	
Safety	IEC-62103 (class II safety), VDE0126-5, UL1741	
Material	UL-94 (5-VA), UV Resistant	
RoHS	Yes	
INSTALLATION SPECIFICATIONS		
Dimensions (WxLxH)	200x141x25 / 7.9x5.6x1	mm / in
Weight	700 / 1.5	g / lb
Operating Temperature Range	-40 - +65 / -40 - +150	°C / °F
Protection Rating	IP65 Outdoor Use / NEMA 3R	
Relative Humidity	0 - 100	%

*CSI power optimizer warranty will not extend beyond the warranty period of the module in which it is embedded.

USA 900 Golden Gate Terrace, Suite E, Grass Valley CA 95945, USA
Germany Bretonischer Ring 18, 85630 Grasbrunn (Munich), Germany
Japan B-9 Ariake Frontier Building, 3-7-26 Ariake, Koto-Ku, Tokyo 135-0063, Japan
Israel 6 HeHarash St. P.O.Box 7349, Neve Neeman, Hod Hasharon 45240, Israel

www.solaredge.com



solaredge
architects of energy™